



T25XWTC Yamaha 4 Stroke 25hp Extra-Long Shaft HIGH THRUST, Electric Start, Power Trim & Tilt System, Multi-Functional Tiller Handle or Forward Control OUTBOARD FOR SALE

The new T25 benefits from the technology and features available on the standard F25 model, including an exceptional power-to-weight ratio, variable trolling rpm control and the ability to connect to Yamaha's Command Link Digital Gauges.

- T25LWTC- High Thrust, Electric Start, Multi-Functional Tiller Handle or Power Tilt System(Foreward Control), Transom height - Long
- T25XWTC- High Thrust, Electric Start, Multi-Functional Tiller Handle or Power Tilt System(Foreward Control), Transom height - Extra-Long

- CDI Microcomputer

- Wet Sump Lubrication
  - Engine Warning System
  - Mechanical Single Throttle Valve Intake System
  - SST Drive, Prop, Shift Shafts
  - SST Steering Tube
  - Magnetic Drain Plug
  - Sacrificial Anodes
  - YDC-30 Aluminum Alloy
  - Phaze Five™ Paint System
  - Electro-deposited Powerhead Paint Process
- CONVENIENCE/CONTROL
- High-Output (16-Amp) Alternator
  - 45-Degree Steering in both Directions

- Built-In Resting Pads and Carry Handles
- Variable Trolling RPM Switch (VTS®)
- Freshwater Flush
- Spin-on Oil Filter
- Offset Steering Friction Lever
- Auto Decompression Device
- Vibration Reduction Mounting System
- C.A.R.B. Ultra Low Emissions 3 Star Rating
- External Oil Drain Plug
- Dual Thrust Propeller

Specifications

ENGINE

Engine TypeTwo-cylinder, In-line

Displacement432 cc

Bore x Stroke65 x 65.1 mm

Full Throttle RPM Range5000 – 6000

Variable Trolling RPM Range750–1050 rpm

750–1050 rpm900 rpm

Horsepower Rating at Propshaft25 hp at 5500 rpm

Compression Ratio9.3:1

Fuel Induction/ScavengingSOHC, 2 valves per cylinder

Alternator Output16 amp

Starting MethodE = Electric Start with Manual Backup

IgnitionCDI Microcomputer

LubricationWet Sump

Degree of Trim-3° through +16° (PTT)

Degree of Tilt-3° through +63° (PTT)

ExhaustThrough Propeller

CoolingWater, Thermostatic Control

DRIVE

Gear ShiftF-N-R (Forward-Neutral-Reverse)

Gear Ratio2.08:1

SHAFT LENGTH

See Model CodeL = 20" X = 25"

FUEL AND LUBRICATION

Recommended FuelRegular Unleaded

Recommended Fuel FiltrationYamaha 10-Micron or Mini-10TM

Recommended OilYamalube® 4-M 10w-30

Engine Oil Capacity1.1L / 1.0L (w/without filter)

LIMITED WARRANTY

Recreational 2 + 2 Years

Commercial 1 Year

WEIGHT

- T25LWTC = 64 kg
- T25XWTC = 70 kg

\*Weight estimated at time of publishing includes standard propeller, which is included with this model. Weight is measured without motor and gearcase oil.

Prices do not include fitting or accessories where applicable.

It is a Yamaha Australia stipulation that all Yamaha Outboards be fitted and personally delivered by the selling Yamaha outboard dealership.

Boat Brand	Model	Stock Number
Yamaha	T25XWTC	0
Length	Year	Condition
0.00 Metres	2022	New
State	Suburb	Boat Link
Queensland	BURPENGARY	